

Wall mounted unit

Discreet wall mounted unit providing high efficiency and comfort

- Practically inaudible: the unit runs so quietly, you will almost forget it is there.
- Onecta app: control your indoor from any location with an app, via your local network or internet.
- Voice command via Amazon Alexa or Google Assistant to control main functions such as set point, operation mode, fan speed, etc
- Silver allergen removal and air purifying filter captures allergens such as pollen to ensure a steady supply of clean air
- 3-D air flow combines vertical and horizontal auto swing to circulate a stream of warm or cool air right to the corners of even large spaces
- The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- Seasonal efficiency values up to A++ in cooling and heating
- Space saving contemporary wall mounted design



- Up to 3 indoor units can be connected to 1 multi outdoor unit; all indoor units are individually controllable and do not need to be installed in the same room or at the same time. They operate simultaneously within the same heating or cooling mode.

More details and final information can be found by scanning or clicking the QR codes.



FTXP-N



RXP-N

Efficiency data				FTXP + RXP	20N + 20N	25N + 25N	35N + 35N	50N + 50N	60N + 60N	71N + 71N	
Cooling capacity	Min./Nom./Max.			kW	1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	1.7/5.0/6.0	1.7/6.0/7.0	2.3/7.1/7.3	
Heating capacity	Min./Nom./Max.			kW	1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	1.7/6.0/7.7	1.7/7.0/8.0	2.3/8.2/9.0	
Power input	Cooling	Min./Nom./Max.		kW	0.31/0.54/0.72	0.31/0.67/0.72	0.29/1.08/1.30	0.320/1.385/1.826	0.332/1.824/2.980	0.449/2.689/3.274	
	Heating	Min./Nom./Max.		kW	0.25/0.52/0.95	0.25/0.69/0.95	0.29/0.99/1.29	0.440/1.579/2.356	0.456/1.928/2.787	0.617/2.571/3.306	
Space cooling	Energy efficiency class							A**			
	Capacity	Pdesign		kW	2.00	2.50	3.50	5.0	6.0	7.1	
	SEER					7.20		7.30	6.82	6.20	
	Annual energy consumption			kWh/a	97	121	170	240	308	401	
Space heating (Average climate)	Energy efficiency class					A**			A*		
	Capacity	Pdesign		kW	2.20	2.40	2.80	4.60	4.80	6.20	
	SCOP/A				4.65	4.61	4.64	4.40	4.10	4.01	
	Annual energy consumption			kWh/a	663	728	845	1,463	1,638	2,166	
Nominal efficiency	EER				3.75		3.26	3.61	3.29	2.64	
	COP				4.77	4.36	4.02	3.80	3.63	3.19	
	Annual energy consumption			kWh	270	335	540	693	912	1,345	
	Energy labeling Directive	Cooling/Heating				A/A			-/-		
Indoor unit				FTXP	20N	25N	35N	50N	60N	71N	
Dimensions	Unit	HeightxWidthxDepth		mm	286x770x225			295x990x263			
Weight	Unit			kg	8.50			13.5			
Air filter	Type				Removable / washable						
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m³/min	4.2/5.6/7.4/9.5	4.2/5.8/7.7/9.7	4.5/6.3/8.3/11.5	8.3/11.5/14.0/16.3	9.2/11.8/14.4/16.8	10.1/11.8/14.4/16.8	
		Heating	Silent operation/ Low/Medium/High	m³/min	5.2/6.2/8.1/10.4	5.2/6.4/8.1/10.4	5.3/7.0/9.0/11.5	10.4/11.8/14.4/17.3	11.0/12.4/15.3/17.9		
Sound power level	Cooling			dBA	55		58	59	60	62	
	Heating			dBA	55		58	61	62		
Sound pressure level	Cooling	Silent operation/Low/High		dBA	19/25/39	19/26/40	20/27/43	27/34/43	30/36/45	32/37/46	
	Heating	Silent operation/Low/High		dBA	21/28/39	21/28/40	21/29/40	30/38/42	32/40/44	33/41/45	
Control systems	Infrared remote control				ARC480A53						
Outdoor unit				RXP	20N	25N	35N	50N	60N	71N	
Dimensions	Unit	HeightxWidthxDepth		mm	550x740x343			734x870x373			
Weight	Unit			kg	26			46.0	50.0		
Sound power level	Cooling				60			62	61	63	66
Sound pressure level	Cooling	Nom.		dBA	46			48	47	49	52
	Heating	Nom.		dBA	47			48	49		52
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~48						
	Heating	Ambient	Min.~Max.	°CWB	-15~18						
Refrigerant	Type				R-32						
	GWP				675.0			675			
Piping connections	Charge			kg/TCO2Eq	0.55/0.37		0.70/0.48	0.90/0.61	1.15/0.78		
	Liquid	OD		mm	6.4			6.35			
	Gas	OD		mm	9.5			12.7			
	Piping length	OU - IU	Max.	m	20			30			
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)						
	Level difference	IU - OU	Max.	m	12			20			
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240						
Current - 50Hz	Maximum fuse amps (MFA)			A	16			20			

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for electrical data | See separate drawing for operation range | Contains fluorinated greenhouse gases

** Integrated for 20-25-35 class. Standard for 50-60-71 class